

## Product Bulletin

# Tag-it™ HF-I Standard Transponder Inlays

### Description

Texas Instruments' Tag-it HF-I Standard transponder inlays consist of 13.56-MHz high-frequency (HF) transponders that are compliant with the ISO/IEC 15693 and ISO/IEC 18000-3 global open standards. These products offer a user accessible memory of 256 bits, organized in eight blocks and an extensive command set available in five different antenna shapes with frequency offset for integration into paper, PVC or other substrates.

Tag-it HF-I Standard transponder inlays are manufactured with TI's patented laser-tuning process to provide consistent read performance. Prior to delivery, the transponders undergo complete functional and parametric testing, in order to provide the high quality customers have come to expect from TI.


The Tag-it HF-I Standard transponder inlays are well suited for a variety of applications including, but not limited to, product authentication, library applications, supply chain management, asset management and ticketing/stored value applications.

### Key Features

- ISO/IEC 15693 -2,-3; ISO/IEC18000-3
- 256-bit user memory, 8x32 bit
- User and factory lock per block
- Application Family Identifier (AFI)
- FastSID

### Tag-it™ HF-I Standard Product Specifications

Supported Standards	ISO/IEC 15693-2, -3; ISO/IEC18000-3
Recommended Operating frequency	13.56 MHz
Factory programmed Read Only Number	64 bits
Memory (user programmable)	256 bits organized in 8x32-bit blocks
Typical programming cycles (at +25°C)	100,000
Data retention time (at +55°C)	>10 years
Delivery	Single row tape wound on cardboard reel



Tag-it™ HF-I Standard transponder inlays are available in a variety of package options, including square, circular and rectangular (regular and mini).

### Tag-it™ HF-I Standard Transponder Inlays

Part Number	RI-I11-114A-01	RI-I11-114B-01	RI-I02-114A-01	RI-I02-114B-01	RI-I03-114-01	RI-I16-114-01	RI-I17-114-01
Available Memory	256 bits organized in 8 x 32-bit blocks						
Foil width (mm)	48 mm ± 0.5 mm						
Antenna size (mm)	45 x 45	45 x 45	45 x 76	45 x 76	22.5 x 38	Ø 24.2	Ø 32.5
Foil pitch (mm)	50.8 +0.1/-0.4 (2in)	50.8 +0.1/-0.4 (2in)	96 +0.1/-0.4 (~3.78 in)	96 +0.1/-0.4 (~3.78 in)	48 +0.1/-0.4 (~1.89 in)	50.8 +0.1/-0.4 (2in)	50.8 +0.1/-0.4 (2in)
Frequency Offset for lamination material	Paper	PVC	Paper	PVC	Paper/PVC	Paper/PVC	Paper/PVC
Delivery	Single row tape wound on cardboard reel						

For more information, contact the sales office or distributor nearest you. This contact information can be found on our web site at: <http://www.ti-rfid.com>

Texas Instruments reserves the right to change its products and services at any time without notice. TI provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customers products. Therefore, TI assumes no responsibility for customer product design or for infringement of patents and/or the rights of third parties, which may result from assistance provided by TI.

© Copyright 2005 Texas Instruments Incorporated.

11-09-22-160 12/05

# TI Worldwide Technical Support

## Internet

### TI RFID Product Information Center

#### Homepage

[www.ti.com/rfid](http://www.ti.com/rfid)

### US and Canada Product Information Center

Phone: 800-962-7343

Fax: 214-567-7343

Business Hours (Central Standard Time):

Mon. 8:00 am - 5:00 pm

Tues. 10:00 am - 5:00 pm

Wed. 8:00 am - 5:00 pm

Thurs. 10:00 am - 5:00 pm

Fri. 8:00 am - 5:00 pm

E-mail: [rfidsupport@ti.com](mailto:rfidsupport@ti.com)

(Use this email address for follow-up support or questions. For first time inquiries, use the Help Form located at

[www.ti.com/rfid/docs/customer/helpform.shtml](http://www.ti.com/rfid/docs/customer/helpform.shtml).)

## Texas Instruments

### Radio Frequency Identification Systems

6550 Chase Oaks Blvd., MS 8470

Plano, Texas 75023

USA

### European Product Information Center

Country

Phone

Belgium (English)

+32 (0)2 7455455

France (English)

+33 4 93 22 22 00

Germany

+49 (0)8161 80 2200

Italy

+39 (0)39 6568 210

Netherlands (English)

+31 (0)546 879 222

Spain

+34 902 19 73 96

Sweden (English)

+46 (0)8 58755527

UK

+44 (0)1604 88 4088

Fax:

All Languages — +49 (0) 8161 80 2045

Business Hours (Central European Time):

Mon. 8:30 am - 17:30 pm

Tues. 8:30 am - 17:30 pm

Wed. 8:30 am - 17:30 pm

Thurs. 8:30 am - 17:30 pm

Fri. 9:00 am - 16:00 pm

E-mail: [e-rfidsupport@ti.com](mailto:e-rfidsupport@ti.com)

## Texas Instruments

### Radio Frequency Identification Systems

#### – European Product Information Center

Deutschland GmbH

Haggertystrasse 1D-85350 Freising

Germany

### International Product Information Center

Phone: +1 972-575-4364 (English)

Fax: 214-567-2492

Business Hours (Central Standard Time):

Monday - Friday 8:00 am - 5:00 pm

E-mail: [rfidsupport@ti.com](mailto:rfidsupport@ti.com)

## Texas Instruments

### Radio Frequency Identification Systems

6550 Chase Oaks Blvd., MS 8470

Plano, Texas 75023

USA

**Important Notice:** The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

Technology for Innovators and the black/red banner are trademarks of Texas Instruments.

All other trademarks are the property of their respective owners.

A011905

© 2005 Texas Instruments Incorporated



SZZT006